

emco Bau

Clean-off system CONFORM

Model	CONFORM
	For laying indoors
Construction	Tufting-Velours 1/8"
Pile above substrate	100% polyamide ECONYL
Substrate material	Polyester fleece
Backing material	Heavy coating
Pile weight / fibre weight	1200 g/m ²
Total weight (g/m ²)	3710 g/m ²
Overall height (mm)	9 mm
Combustion/fire behaviour	Cfl-s1
Slip resistance	DS (EN 13893)
Certificates	CE conformity EN 14041 (rolls only)
Colours	76.01 Anthracite
	76.02 Beige
	Mocha 76.03
	76.04 Brown
	76.10 grey
Colour fastness to artificial light ISO 105-B02	≥5
Colour fastness to rubbing ISO 105 X12	≥4
Colour fastness to water ISO 105 E01	≥4
Bacterial reduction EHEC ASTM-e2149	16,1 %
Bacterial reduction staphylococcus aureus ASTM-e2149	0,0 %
Bacterial reduction klebsiella pneumoniae ASTM-e2149	65,6 %
Supplied as rolls	130 cm wide (incl. border)
	200 cm wide (incl. border)
Supplied as mats	60 x 90 cm (incl. border)
	90 x 150 cm (incl. border)
	130 x 200 cm (incl. border)
Supplied as stair mat	25 x 65 cm (with non-slip nonwoven fabric and merrow border)
Product characteristics	Soiling and moisture absorption
Brand	emco

Dimensions

Width:.....m

Length:.....m

Contact

emco Bautechnik GmbH · Memeler Straße 30 · D-42781
Haan · Germany · Tel.: +49 (0)21 29/34 75 80 · Telefax: +49
(0)21 29/34 75 810 · E-Mail: sauberlauf@emco.de · [www.
emco-bau.com](http://www.emco-bau.com)