

## emco Bau

### Clean-off system MAXIMUS®

<b>Model</b>	MAXIMUS® For laying indoors
<b>Construction</b>	Tufting-Velours 1/8"
<b>Pile above substrate</b>	100% polyamide
<b>Substrate material</b>	Polyester fleece
<b>Backing material</b>	Heavy coating
<b>Pile weight / fibre weight</b>	1000 g/m <sup>2</sup>
<b>Total weight (g/m<sup>2</sup>)</b>	3410 g/m <sup>2</sup>
<b>Overall height (mm)</b>	9 mm
<b>Combustion/fire behaviour</b>	Bfl-s1
<b>Slip resistance</b>	DS (EN 13893)
<b>Certificates</b>	CE conformity EN 14041 (rolls only)
<b>Colours</b>	83.02 anthracite 83.03 grey 83.04 brown 83.05 beige 83.07 red Black 80.01 Black mottled 81.01 Anthracite 80.02 Anthracite mottled 81.02 Grey 80.03 Brown 80.04 Brown mottled 81.04 Red 80.07
<b>Colour fastness to artificial light ISO 105-B02</b>	≥5
<b>Colour fastness to rubbing ISO 105 X12</b>	≥4
<b>Colour fastness to water ISO 105 E01</b>	≥4
<b>Bacterial reduction EHEC ASTM-e2149</b>	29,4 %
<b>Bacterial reduction staphylococcus aureus ASTM-e2149</b>	16,7 %
<b>Bacterial reduction klebsiella pneumoniae ASTM-e2149</b>	68,2 %

<b>Supplied as rolls</b>	130 cm wide (incl. border) 200 cm wide (incl. border)
<b>Supplied as mats</b>	60 x 90 cm (incl. border) 90 x 150 cm (incl. border) 130 x 200 cm (incl. border)
<b>Product characteristics</b>	Soiling and moisture absorption
<b>Brand</b>	emco
<b>Dimensions</b>	Width:.....m Length:.....m
<b>Contact</b>	emco Bautechnik GmbH · Memeler Straße 30 · D-42781 Haan · Germany · Tel.: +49 (0)21 29/34 75 80 · Telefax: +49 (0)21 29/34 75 810 · E-Mail: sauberlauf@emco.de · www. emco-bau.com