

## emco Bau

### Clean-off system PRESTIGE

<b>Model</b>	PRESTIGE For laying indoors
<b>Construction</b>	Tufting-Velours 1/8"
<b>Pile above substrate</b>	100% polyamide ECONYL
<b>Substrate material</b>	Polyester fleece
<b>Backing material</b>	Heavy coating
<b>Pile weight / fibre weight</b>	975 g/m <sup>2</sup>
<b>Total weight (g/m<sup>2</sup>)</b>	3560 g/m <sup>2</sup>
<b>Overall height (mm)</b>	8 mm
<b>Combustion/fire behaviour</b>	Cfl-s1
<b>Slip resistance</b>	DS (EN 13893)
<b>Certificates</b>	CE conformity EN 14041 (rolls only)
<b>Colours</b>	61.01 anthracite 61.02 grey 61.03 brown 61.05 blue 61.06 beige
<b>Colour fastness to artificial light ISO 105-B02</b>	≥5
<b>Colour fastness to rubbing ISO 105 X12</b>	≥4
<b>Colour fastness to water ISO 105 E01</b>	≥4
<b>Supplied as rolls</b>	130 cm wide (incl. border) 200 cm wide (incl. border)
<b>Product characteristics</b>	Soiling and moisture absorption
<b>Brand</b>	emco
<b>Dimensions</b>	Width:.....m Length:.....m
<b>Contact</b>	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 Email: bau@emco.de · www.emco-bau.com