

# emco Bau

## PREMIUM

Model	PREMIUM
Construction	Tufting velour 5/32"
Pile above substrate	100% polyamide
Substrate material	Polyester fleece
Backing material	Heavy coating
Pile weight / fibre weight	2050 g/m <sup>2</sup>
Total weight (g/m <sup>2</sup> )	4670 g/m <sup>2</sup>
Overall height (mm)	11 mm
Slip resistance	DS (EN 13893)
Certificates	CE conformity EN 14041 (rolls only)
Colour fastness to artificial light ISO 105-B02	excellent 7
Colour fastness to rubbing ISO 105 X12	good 5
Colour fastness to water ISO 105 E01	good 5
Supplied as rolls	200 cm wide (incl. border)
Product characteristics	Soiling and moisture absorption
Brand	emco
Contact	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com
Type of dirt	Street dust, hair, sand, ash, textile fibres, small leaves and twigs, etc. Damp street dust, damp sand deposits, dust, etc.
Combustion/fire behaviour	Cfl-s1
Colours	75.01 Anthracite 75.03 Beige 75.11 Black 75.12 Red 75.15 Slate