

emco Bau

emco dirt collection well 5000 AL

Model	5000 AL
Weight (kg/m²)	13,0
Structure	Max. one-piece tray segment 2800 x 1300 mm. A dirt collection well unit can be built up in modules consisting of either a single well or multiple wells which may vary in width and depth. From a visual and functional perspective, the entrance mat is commonly manufactured with a frame.
Freedom to create your own individual design	In spite of the rectangular shape of the wells, no limits are placed on your creativity when it comes to tailoring the mat to your own specifications. Architecturally inviting entrances demand a harmoniously integrated entrance mat. In these cases, the wells are often only used in areas where the greatest amounts of dirt occur, and the entrance mats far exceed what is required.
Material	Aluminium (AlMg 1), bonded and waterproof, interior completely smooth for easy cleaning. Also available in stainless steel (V2A) on request.
Support profile	Aluminium (AlMgSi 0.5), stainless steel (V2A), max. spacing 300 mm with recesses for all-around water drainage. These profiles must run laterally at an angle of 90° beneath the profiles.
Additional data	Without surrounding edging frame for the entrance mat. MARSCHALL type 517 S / 522 S and PLAZA type 542 S are larger due to their special design and can be fitted with an additional frame on request.
Larger dimensions	Several well components are screwed together on site to form a single system.
Fittings	With welded wall anchors; drainage system available on request.
Drainage system	Complete drainage system, consisting of a flat outlet (Ø 80 mm) made from stainless steel, and a plastic lower part for subsequent connection to the drainage system (Ø 1 1/2 inches).
Well height (mm)	53
Well installation height (mm)	61
Max. well width, one piece (mm)	2800
Max. well depth, one piece (mm)	1300

Dimensions

Well width:.....mm

Well depth:.....mm (walking direction)

Contact

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com