

# Model 512 PS Maximus K



The Premium entrance mat with the stylish Maximus insert and its carpet look is characterised by high-quality tufted velour and an exclusive appearance. Particularly suitable for collecting fine dirt. The additional profile provides an extra cleaning effect. Ideal for buildings with normal to heavy loads.

- 1
  - 2
  - 3
- Indoor and outdoor (covered, Zone 1+2)

**Description**

Rollable, extremely hard-wearing, premium entrance mat with performance insert for supported installation options. Also capable of withstanding wheeled traffic. Customisable widths and walking depths available without a compensation profile. Available in any geometric shape.

				
Indoor and outdoor (covered, Zone 1+2)	Street dust, hair, sand, ash, textile fibres, small leaves and twigs, etc.	Damp street dust, damp sand deposits, dust, etc.	5 years guarantee	class 32 (general commercial use)

# emco MARSCHALL Premium With Maximus insert and scraping edge

## Model 512 PS Maximus K

<b>Approx. height (mm)</b>	12	<b>Accessories</b>
<b>Roll-over and drive-over capability:</b>	Prams	emco installation frame 500: 500-15 AL Aluminium
	Sack-/hand truck	emco installation frame 500: 500-15 CN Chrome-nickel steel (V2A)
	Wheelchairs	emco ramp edge: A12 Aluminium
<b>Standard profile clearance approx. (mm)</b>	5 mm, rubber spacers	emco cover strip: C12 Chrome-nickel steel (V2A)
<b>Automatic door systems</b>	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005	emco INOX®: LINEO 12 Chrome-nickel steel (V2A)
		Rubber underlay 1 mm: GU 1
<b>Connection</b>	Plastic-coated stainless steel cable	Rubber underlay 3 mm: GU 3
<b>Max. width/profile length for individual section (mm):</b>	3000	Rubber underlay 5 mm: GU 5
		Mat joining brackets: MV Supplied as standard with mats in several parts
<b>Profile width (mm)</b>	30	<b>Suitable for:</b>
<b>Depth/walking depth for individual section (mm):</b>	1500	Residential and care homes
<b>Weight (kg/m<sup>2</sup>)</b>	11,6	medical practice
<b>Mat divisions as per factory standards or customer specifications</b>	from a profile length of 3000 mm or a maximum mat weight of 25 kg	Offices and administrative buildings
		Family home
<b>Support chassis</b>	Reinforced support chassis made using rigid aluminium with Premium sound absorbing insulation on the underside	Retail sector
		Hotel
<b>Tread surface</b>	Embedded, robust MAXIMUS inserts in Bfl-S1 quality (clean-off floor covering made from special polyamide yarn, 100%)	Kindergarten/Nursery
		Apartment building
<b>Flammability</b>	Insert with fire classification Bfl-s1 according to EN 13501.	School
<b>Pile material</b>	100% PA 6.6 (polyamide)	Sports hall
<b>Use classification EN1307</b>	class 33 (heavy commercial use)	<b>Insert certified to TÜV PROFiCERT- product interior (Standard)</b>
		French VOC regulation
		LEED v4 (outside North America)
		BREEAM Exemplary Level
		Belgian VOC regulation
		AgBB (Committee for Health-related Evaluation of Building Products)
		MVV TB Appendix 8, 9 / ABG

## Model 512 PS Maximus K

### Colours



Black 80.01



Black mottled 81.01



Anthracite 80.02



Brown 80.04



Red 80.07

Subject to technical modifications

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems)  
· Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email:  
bau@emco.de · www.emco-bau.com