

emco Bau

emco DIPLOMAT Premium Large With Care insert and scraping edge 517 PL Care K

Model	517 PL Care K
Load	Normal to heavy
Support chassis	Made using rigid aluminium with Premium sound absorbing insulation on the underside
Support chassis colour	Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel
Approx. height (mm)	17
Tread surface	The robust and exceptionally abrasion-resistant Care insert for the effective reduction of fine dirt. The additional profile increases the cleaning power.
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
Colours	47.01 anthracite 47.02 grey 47.03 brown 47.04 beige
Special colours	Other colours from our clean-off collection also available.
Flammability	Insert with fire classification Cfl-s1 according to EN 13501.
Connection	Plastic-coated stainless steel cable
Warranty	5 years guarantee Warranty conditions are available at: www.emco-bau.com/garantiebedingungen/
Insert certified to TÜV PROFICERT-product interior (Standard)	French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG
Pile material	100% PA 6 (polyamide)
Use classification EN1307	class 33 (heavy commercial use)

Colour fastness to artificial light ISO 105-B02 good 5-6

Colour fastness to rubbing ISO 105 X12 good 4-5

Colour fastness to water ISO 105 E01 good 4-5

Dimensions Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

Contact emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com