

emco Bau

emco MARSCHALL Premium Large With Maximus insert and scraping edge 517 PSL Maximus K

| | |
|--|---|
| Model | 517 PSL Maximus K |
| Load | Extremely heavy |
| Support chassis | Reinforced support chassis made using rigid aluminium with Premium sound absorbing insulation on the underside |
| Approx. height (mm) | 17 |
| Tread surface | Embedded, robust MAXIMUS inserts in Bfl-S1 quality (clean-off floor covering made from special polyamide yarn, 100%) |
| Standard profile clearance approx. (mm) | 5 mm, rubber spacers |
| Automatic door systems | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 |
| Colours | Anthracite 80.02 Brown 80.04 Red 80.07 Black mottled 81.01 Black 80.01 |
| Special colours | Other colours from our clean-off collection also available. |
| Flammability | Insert with fire classification Bfl-s1 according to EN 13501. |
| Connection | Plastic-coated stainless steel cable |
| Warranty | 5 years guarantee |
| Insert certified to TÜV PROFiCERT-product interior (Standard) | French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG |
| Pile material | 100% PA 6.6 (polyamide) |
| Use classification EN1307 | class 33 (heavy commercial use) |
| Dimensions | Mat width:.....mm (bar length) Mat depth:.....mm (walking direction) |
| Contact | emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · |

