

emco Bau

emco DIPLOMAT Premium With Maximus Image insert and brush strip 517 P Maximus Image B

Model	517 P Maximus Image B
Load	Normal to heavy
Support chassis	Made using rigid aluminium with Premium sound absorbing insulation on the underside
Approx. height (mm)	17
Tread surface	The Maximus Image insert is suitable for single-colour printing in a personally chosen colour. The additional profile increases the cleaning effect.
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
Colours	I350 Blue grey I80 Bordeaux I260 Brown I380 Dark grey I210 Dark green I120 Lilac I30 Yellow/orange I20 Yellow I420 Gold I270 Graphite I340 Grey beige I370 Grey I250 Green I170 Light blue I360 Light grey I440 Light green I90 Light red I100 Cherry I430 Salmon pink I230 Leaf green I290 Light blue I110 Purple

I140 Magenta
I200 Marine blue
I330 Chestnut
I220 Mint
I40 Orange
I70 Oxide red
I180 Petrol blue
I150 Peach
I310 Fawn brown
I60 Red
I160 Royal blue
I320 Sand
I240 Reed green
I390 Black
I300 Silver
I190 Emerald green
I280 Steel blue
I410 Steel grey
I450 Sunset
I50 Terracotta
I130 Grape
I400 White*
I10 Lemon

grey

Black

Special colours

Other colours from our clean-off collection also available.

Connection

Plastic-coated steel cable

Warranty

5 years guarantee

Insert certified to TÜV PROFiCERT-product interior (Standard)

French VOC regulation

LEED v4 (outside North America)

BREEAM Exemplary Level

Belgian VOC regulation

AgBB (Committee for Health-related Evaluation of Building Products)

MVV TB Appendix 8, 9 / ABG

Pile material

100% PA 6.6 (polyamide)

Use classification EN1307

class 33 (heavy commercial use)

Dimensions

Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)



Contact

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-
49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-
500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de ·
www.emco-bau.com