

emco Bau

emco DIPLOMAT Premium With Outdoor insert and scraping edge 517 P Outdoor K

Model	517 P Outdoor K
Load	Normal to heavy
Support chassis	Made using rigid aluminium with Premium sound absorbing insulation on the underside
Approx. height (mm)	17
Tread surface	The weather-resistant Outdoor insert for noticeably thorough removal of coarse dirt. The additional profile increases the cleaning power.
Standard profile clearance approx. (mm)	5 mm, rubber spacers
Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
Colours	Anthracite Brown Red
Flammability	Insert with fire classification Cfl-s1 according to EN 13501.
Connection	Plastic-coated stainless steel cable
Warranty	5 years guarantee
Pile material	100% PA 6 (polyamide)
Use classification EN1307	class 33 (heavy commercial use)
Dimensions	Mat width:.....mm (bar length) Mat depth:.....mm (walking direction)
Contact	emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com