

## emco Bau

### emco DIPLOMAT Premium Large With Innova insert 522 PL Innova

<b>Model</b>	522 PL Innova
<b>Load</b>	Normal to heavy
<b>Support chassis</b>	Made using rigid aluminium with Premium sound absorbing insulation on the underside
<b>Approx. height (mm)</b>	22
<b>Tread surface</b>	The exceptionally flexible Innova insert not only creates a sophisticated impression but also improves room acoustics.
<b>Standard profile clearance approx. (mm)</b>	5 mm, rubber spacers
<b>Automatic door systems</b>	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005
<b>Slip resistance</b>	R 12 slip resistance as per DIN 51130
<b>Colours</b>	36.02 anthracite 36.03 grey 36.01 black
<b>Special colours</b>	Other colours from our clean-off collection also available.
<b>Flammability</b>	Fire classification for the complete mat system Cfl-s1 in accordance with EN 13501
<b>Connection</b>	Plastic-coated stainless steel cable
<b>Warranty</b>	5 years guarantee
<b>Insert certified to TÜV PROFiCERT-product interior (Standard)</b>	French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building Products) MVV TB Appendix 8, 9 / ABG
<b>Pile material</b>	100% PA 6 (polyamide)
<b>Use classification EN1307</b>	class 33 (heavy commercial use)
<b>Colour fastness to artificial light ISO 105-B02</b>	good 5-6
<b>Colour fastness to rubbing ISO 105 X12</b>	good 4-5
<b>Colour fastness to water ISO 105 E01</b>	good 4-5
<b>Bacterial reduction EHEC ASTM-e2149</b>	8,4 %

**Bacterial reduction staphylococcus aureus ASTM-e2149** 51,7 %

**Bacterial reduction klebsiella pneumoniae ASTM-e2149** 83,6 %

**Dimensions** Mat width:.....mm (bar length)

Mat depth:.....mm (walking direction)

**Contact** emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com