

emco Bau

emco MARSCHALL Premium Large With MAXIMUS insert 522 PSL Maximus

| | |
|--|---|
| Model | 522 PSL Maximus |
| Load | Extremely heavy |
| Support chassis | Reinforced support chassis made using rigid aluminium with Premium sound absorbing insulation on the underside |
| Support chassis colour | Aluminium as standard. Anodised colours for an additional charge: EV3 gold, C33 mid-bronze, C35 black or C31 stainless steel |
| Approx. height (mm) | 22 |
| Note on height | The insert can actually be approx. 2-3 mm higher due to the wear layer. |
| Tread surface | Embedded, robust MAXIMUS inserts in Bfl-S1 quality (clean-off floor covering made from special polyamide yarn, 100%) |
| Standard profile clearance approx. (mm) | 5 mm, rubber spacers |
| Automatic door systems | Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005 |
| Slip resistance | R 12 slip resistance as per DIN 51130 |
| Colours | Anthracite 80.02 Brown 80.04 Red 80.07 Black mottled 81.01 Black 80.01 |
| Special colours | Other colours from our clean-off collection also available. |
| Flammability | Fire classification for the complete mat system Bfl-s1 in accordance with EN 13501 |
| Connection | Plastic-coated stainless steel cable |
| Warranty | 5 years guarantee Warranty conditions are available at: www.emco-bau.com/garantiebedingungen/ |
| Insert certified to TÜV PROFICERT-product interior (Standard) | French VOC regulation LEED v4 (outside North America) BREEAM Exemplary Level Belgian VOC regulation AgBB (Committee for Health-related Evaluation of Building |

| | |
|---|--|
| | Products) |
| | MVV TB Appendix 8, 9 / ABG |
| Pile material | 100% PA 6.6 (polyamide) |
| Use classification EN1307 | class 33 (heavy commercial use) |
| Colour fastness to artificial light ISO 105-B02 | good 5-6 |
| Colour fastness to rubbing ISO 105 X12 | good 5 |
| Colour fastness to water ISO 105 E01 | good 5 |
| Bacterial reduction EHEC ASTM-e2149 | 29,4 % |
| Bacterial reduction staphylococcus aureus ASTM-e2149 | 16,7 % |
| Bacterial reduction klebsiella pneumoniae ASTM-e2149 | 68,2 % |
| Dimensions | Mat width:.....mm (bar length) Mat depth:.....mm (walking direction) |
| Contact | emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems) · Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email: bau@emco.de · www.emco-bau.com |