

Model 522 PS Outdoor K



The weather-resistant premium entrance mat with the Outdoor insert for noticeably thorough removal of coarse dirt. The additional profile offers even more cleaning power. Optimally designed for buildings exposed to extreme footfall.



Description

Roll-up, extremely hard-wearing Premium entrance mat with Performance insert for surface installation. Customisable width and depth without alignment profile. Available in any geometric shape.



Outside (Zone 1)



Street dust, hair, sand, ash, textile fibres, small leaves and twigs, loose chippings, coarse sand, small gravel particles



5 years guarantee



class 33 (heavy commercial use)

emco MARSCHALL Premium With Outdoor insert and scraping edge

Model 522 PS Outdoor K

Approx. height (mm)	22	Accessories
Roll-over and drive-over capability:	Prams	emco installation frame 500: 500-25 AL Aluminium
	Sack-/hand truck	emco installation frame 500: N500-25 AL Aluminium
	Wheelchairs	emco installation frame 500: 500-25 CN Chrome-nickel steel (V2A)
Standard profile clearance approx. (mm)	5 mm, rubber spacers	emco installation frame 500: N500-25 CN Chrome-nickel steel (V2A)
Automatic door systems	Profile clearance of 3 mm available as an option for revolving door drives, in accordance with EN 16005	emco LUMINA: LUMINA + LED Aluminium
Connection	Plastic-coated stainless steel cable	emco LUMINA: LUMINA Aluminium
Max. width/profile length for individual section (mm):	3000	emco LUMINA: LUMINA VIA Aluminium
Profile width (mm)	30	emco ramp edge: A17 Aluminium
Depth/walking depth for individual section (mm):	3000	emco T-profile: T22
Weight (kg/m²)	16,5	emco cover strip: C22 Chrome-nickel steel (V2A)
Mat divisions as per factory standards or customer specifications	As of a profile length of 3000 mm or a maximum mat weight of 45 kg	emco INOX®: LINEO 22 Chrome-nickel steel (V2A)
Support chassis	Reinforced support chassis made using rigid aluminium with Premium sound absorbing insulation on the underside	emco INOX®: QUADRO 22 Chrome-nickel steel (V2A)
Tread surface	The weather-resistant Outdoor insert for noticeably thorough removal of coarse dirt. The additional profile increases the cleaning power.	Rubber underlay 1 mm: GU 1
Flammability	Insert with fire classification Cf1-s1 according to EN 13501.	Rubber underlay 3 mm: GU 3
Pile material	100% PA 6 (polyamide)	Rubber underlay 5 mm: GU 5
Use classification EN1307	class 33 (heavy commercial use)	Mat joining brackets: MV Supplied as standard with mats in several parts
		Suitable for:
		Residential and care homes
		Arena
		medical practice
		Train station
		DIY store
		Offices and administrative buildings
		Family home
		Shopping centre
		Retail sector
		University / Higher education institution
		airport
		Hotel
		Industry
		Kindergarten/Nursery
		Warehouse
		Apartment building
		Trade fair
		School
		Sports hall

Model 522 PS Outdoor K

Service and services	Installation service
Construction site advice	Fitting and installation service
Dimensioning	Repairs
Measured using laser measuring device on site.	The product can be disposed of or recycled in an environmentally friendly way.

Model 522 PS Outdoor K

Colours



Anthracite



Brown



Red

Subject to technical modifications

emco Bautechnik GmbH · Breslauer Straße 34 - 38 · D-49808 Lingen (Ems)
· Germany · Phone: +49 (0) 591/9140-500 · Fax: +49 (0) 591/9140-852 · Email:
bau@emco.de · www.emco-bau.com

