

**emco Bau****Clean-off system CONFORM TILES**

<b>Model</b>	CONFORM TILES For laying indoors
<b>Construction</b>	Tufting-Velours 1/8"
<b>Pile above substrate</b>	100% polyamide ECONYL
<b>Substrate material</b>	Polyester fleece
<b>Backing material</b>	Bitumen
<b>Pile weight / fibre weight</b>	1200 g/m <sup>2</sup>
<b>Total weight (g/m<sup>2</sup>)</b>	4260 g/m <sup>2</sup>
<b>Overall height (mm)</b>	9 mm
<b>Combustion/fire behaviour</b>	Bfl-s1
<b>Slip resistance</b>	DS (EN 13893)
<b>Certificates</b>	CE conformity EN 14041 (rolls only)
<b>Colours</b>	76.01 Anthracite 76.02 Beige Mocha 76.03 76.04 Brown 76.10 grey
<b>Colour fastness to artificial light ISO 105-B02</b>	≥5
<b>Colour fastness to rubbing ISO 105 X12</b>	≥4
<b>Colour fastness to water ISO 105 E01</b>	≥4
<b>Supplied as tiles</b>	approx. 50 x 50 cm without a border (with asphalt coating)
<b>Product characteristics</b>	Soiling and moisture absorption
<b>Brand</b>	emco
<b>Contact</b>	emco Bautechnik GmbH · Memeler Straße 30 · D-42781 Haan · Germany · Tel.: +49 (0)21 29/34 75 80 · Telefax: +49 (0)21 29/34 75 810 · E-Mail: sauberlauf@emco.de · www. emco-bau.com