

Model CONFORM SE



Description

Exclusive velour, recycled ECONYL yarn, tailored to suit appearance of wood and designer floors, low-flammability version: fire classification Bfl-s1



Anti-static



Castor-resistant



Suitable for stairs



DS (EN 13893)



Resistant strength



Cfl-s1



Luxurious



Highly suitable for property

Colours



76.01 Anthracite



76.02 Beige



Mocha 76.03



76.04 Brown



76.05 Blue



76.06 Aubergine

Model CONFORM SE

Construction	Tufting-Velours 1/8"
Pile above substrate	100% polyamide 6 ECONYL
Substrate material	Polyester fleece
Backing material	Synthetic latex
Pile weight / fibre weight	1200
Total weight (g/m²)	2400
Overall height (mm)	8.5
Tuft density/m²	132280
Slip resistance	DS (EN 13893)
Certificates	CE conformity EN 14041 (rolls only)
Supplied as rolls SE/Bfi-s1	400 cm wide (no border)
Product characteristics	Soiling and moisture absorption
Laying	Individual rolls or smaller coverings can be laid loose on any smooth floor. For larger areas, and allowing for on-site conditions, we recommend fixed laying with an adhesive suitable for plasticised PVC.
Cleaning	Dirt removal with powerful brush vacuum cleaner. The spray extraction process is recommended for periodic basic cleaning. Cleaning with plenty of water is absolutely no problem, water temperature should not be above 40°C. Do not use chlorinated hydrocarbon (Tetra).
Brand	emco