

Model CONFORM



Description

Exclusive velour, recycled ECONYL yarn, tailored to suit appearance of wood and designer floors.



Anti-static



Castor-resistant



Suitable for stairs



DS (EN 13893)



Resistant strength



Cfl-s1



Luxurious



Highly suitable for property

Colours



76.01 Anthracite



76.02 Beige



Mocha 76.03



76.04 Brown



76.05 Blue



76.06 Aubergine

Model CONFORM

Construction	Tufting-Velours 1/8"
Pile above substrate	100% polyamide 6 ECONYL
Substrate material	Polyester fleece
Backing material	Heavy coating
Pile weight / fibre weight	1200
Total weight (g/m²)	3820
Overall height (mm)	9
Tuft density/m²	132280
Slip resistance	DS (EN 13893)
Certificates	CE conformity EN 14041 (rolls only)
Supplied as rolls	130 cm wide (incl. border) 200 cm wide (incl. border)
Supplied as mats	60 x 90 cm (incl. border) 90 x 150 cm (incl. border) 130 x 200 cm (incl. border)
Supplied as tiles	approx. 50 x 50 cm without a border (with asphalt coating)
Supplied as stair mat	25 x 65 cm (with non-slip nonwoven fabric and merrow border)
Product characteristics	Soiling and moisture absorption
Laying	Individual rolls or smaller coverings can be laid loose on any smooth floor. For larger areas, and allowing for on-site conditions, we recommend fixed laying with an adhesive suitable for plasticised PVC.
Cleaning	Dirt removal with powerful brush vacuum cleaner. The spray extraction process is recommended for periodic basic cleaning. Cleaning with plenty of water is absolutely no problem, water temperature should not be above 40°C. Do not use chlorinated hydrocarbon (Tetra).
Brand	emco