

emco Bau**Clean-off system MAXIMUS®**

Model	MAXIMUS® For laying indoors
Construction	Tufting-Velours 1/8"
Pile above substrate	100% polyamide
Substrate material	Polyester fleece
Backing material	Heavy coating
Pile weight / fibre weight	1000 g/m ²
Total weight (g/m²)	3410 g/m ²
Overall height (mm)	9 mm
Combustion/fire behaviour	Bfl-s1
Slip resistance	DS (EN 13893)
Certificates	CE conformity EN 14041 (rolls only)
Colours	Black 80.01 Black mottled 81.01 Anthracite 80.02 Anthracite mottled 81.02 Grey 80.03 Brown 80.04 Brown mottled 81.04 Red 80.07
Colour fastness to artificial light ISO 105-B02	≥5
Colour fastness to rubbing ISO 105 X12	≥4
Colour fastness to water ISO 105 E01	≥4
Bacterial reduction EHEC ASTM-e2149	29,4 %
Bacterial reduction staphylococcus aureus ASTM-e2149	16,7 %
Bacterial reduction klebsiella pneumoniae ASTM-e2149	68,2 %
Supplied as rolls	130 cm wide (incl. border) 200 cm wide (incl. border)
Supplied as mats	60 x 90 cm (incl. border) 90 x 150 cm (incl. border) 130 x 200 cm (incl. border)



Product characteristics

Brand

Dimensions

Contact

Soiling and moisture absorption

emco

Width:.....m

Length:.....m

emco Bautechnik GmbH · Memeler Straße 30 · D-42781

Haan · Germany · Tel.: +49 (0)21 29/34 75 80 · Telefax: +49

(0)21 29/34 75 810 · E-Mail: sauberlauf@emco.de · [www.](http://www.emco-bau.com)

emco-bau.com